

# DATA SHEET



## IP-DECT Access Point (IPBS3)

### Features

- Connection to IP-PBX via LAN
- Roaming and handover
- DECT GAP/CAP radio interface
- H.323 or SIP protocol over IP
- Secure SIP over TLS and SRTP
- Over the air synchronisation
- Web interface for configuration and software upgrade
- Power over Ethernet or local power supply
- External LED status indication
- Messaging, Alarm and Interactive Messaging
- Broadcast and Multicast Messaging
- Wideband audio
- Eight or four simultaneous calls
- Enhanced DECT Security Step A and Step B (ETSI EN 300 444, N.35, N.36)

## Technical Specifications

### Versions

IPBS3-A3	IP-DECT Base Station with internal antennas
IPBS3-A4	IP-DECT Base Station with external antennas
IPBS3-A5	IP-DECT Base Station with 4 channels internal antennas

### DECT Frequencies

1880–1900 MHz:	Europe, Africa, Middle East, Australia, New Zealand, and parts of Asia
1900–1906 MHz:	Thailand
1910–1930 MHz:	South America
1920–1930 MHz:	North America

### Physical

Dimensions (l × w × d):	170 × 170 × 38 mm (including mounting bracket)
Weight:	Approx. 400 g
Material:	PC/ABS moulded plastic
Colour:	White (NCS S 0502-B)
External connectors:	2 × MCX connectors for external antennas 2 × RJ45 for local power and Ethernet/PoE

### Power

Power over Ethernet IEEE 802.3af or local power supply	
Operating voltage:	21 to 56 VDC
Power consumption:	Typical 4 W, maximum 5 W

### Network

Ethernet:	10/100BaseT
-----------	-------------

*Specifications are subject to change without notice*

Voice over IP	
Voice over IP:	H.323 version 4 incl. H.225, H.235, H.245, H.450 with H.450.1, H.450.2, H.450.3, H.450.4, H.450.6, H.450.7, H.450.8 and H.450.9  RFC 2246, RFC 2396, RFC 2617, RFC 2782, RFC 2833, RFC 3261, RFC 3262, RFC 3263, RFC 3264, RFC 3265, RFC 3280, RFC 3311, RFC 3323, RFC 3325, RFC 3326, RFC 3420, RFC 3515, RFC 3550, RFC 3551, RFC 3555, RFC 3578, RFC 3581, RFC 3680, RFC 3711, RFC 3842, RFC 3891, RFC 3892, RFC 4028, RFC 4235, RFC 4244, RFC 4347, RFC 4538, RFC 4566, RFC 4568, RFC 4730, RFC 4867, RFC 4916, RFC 5245, RFC 5359, RFC 5373, RFC 5389, RFC 5589, RFC 5761, RFC 5763, RFC 5764, RFC 5766, RFC 5806, RFC 5923, RFC 6086, RFC 6188, RFC 7983 draft-ietf-sip-privacy
Voice Encoding:	G.711 A-law / $\mu$ -law (64 kbps) G.722.2 AMR-WB G.729 A and AB (16 kbps)
Radio	
RF output power (e.r.p.), EU:	Between 23 dBm and 28 dBm (with internal antenna)
RF output power (e.r.p.), US:	Between 17 dBm and 21.6 dBm (with internal antenna)
Environmental	
Operating temperature:	-10°C to +55°C
Storage temperature:	-25°C to +70°C
Relative operating humidity:	15% to 90%, non condensing
Relative storage humidity:	5% to 95%, non condensing
Enclosure protection:	IP30
Immunity to electromagnetic fields:	10 V/m (EN 61000-4-3)
Immunity to ESD:	6 kV contact discharge and 8 kV air discharge (EN 61000-4-2)


*Specifications are subject to change without notice*

## Compliance to Regulations and Standards

### Compliance to European and UK Regulations and Standards

Product marking:	
EU directives and regulations:	2014/53/EU (RED) 2015/863 (RoHS3) 2011/65/EU (RoHS)
UK directives and regulations:	Radio Equipment Regulations 2017 RoHS in Electrical and Electronic Equipment Regulations 2012
Radio:	EN 301406
Safety:	EN 62368-1
EMC:	EN 301489-6, EN 301489-1, EN 60945, EN 55032

### Compliance with US and Canadian Regulations and Standards

Product marking:	 FCC ID: BXZIPBS3 IC: 3724B-IPBS3
Safety:	CAN/CSA-C22.2 No 62368-1 UL 62368-1
EMC/Radio:	FCC part 15 (Class B and D) RSS-213 ICES-003

### Compliance to Australian Regulations and Standards

Product marking:	
Safety:	AS/NZS 62368-1
Radio:	Radiocommunications (Digital Cordless Communications Devices – DECT Devices) Standard 2017

EU Declaration of Conformity and UKCA Declaration of Conformity can be found at: <https://www.ascom-ws.com/doc/>

*Specifications are subject to change without notice*

**Ascom (Sweden) AB**

Grimbodalen 2

SE-417 49 Göteborg

Sweden

Phone +46 31 55 93 00

[www.ascom.com](http://www.ascom.com)

**ascom**